



Keunggulan Produk

Performa Maksimal

- Pembakaran dengan CDI yang memudahkan start awal dan tenaga yang besar
- Lulus ketahanan uji coba 800 jam
- Mempunyai kotak transmisi di bawah air untuk mempermudah perawatan dan menstabilkan baling-baling
- Terdapat dua pemasukan air sebagai pendingin sehingga pendinginan sangat efektif
- Karet impeller spesial untuk stabilitas performa
- Anti korosi; Campuran aluminium dan stainless steel

Keamanan

- Dilengkapi dengan "Over-Speed limitation" sistem dan "Drowning-Flame Out" sistem sehingga lebih aman
- Bahan bakar yang efisien dengan sistem "Air-Intake"

Spesifikasi

Engine Style	2 Stroke		
Model #	T15BM	T25BM	T30BM
POWER (HP)	15HP	25HP	30HP
(mm/in) SHAFT LENGTH (L)	520/22	520/22	520/22
CYLINDER TYPE	2 cylinders, 2stroke	2 cylinders, 2stroke	2 cylinders, 2stroke
DISPLACEMENT (cm ³)	259	489	489
BORE x STROKE (mm)	58 x 49	72 x 60	72 x 60
MAX. OUTPUT (hp/kw)	15/11	25/18.4	32/23.5
RPM	4500 ~ 5500	4500 ~ 5500	4500 ~ 5500
COMPRESSION RATIO	6.5	6.5	6.5
SCAVENGING METHOD	Loop	Loop	Loop
IGNITION SYSTEM	CDI	CDI	CDI
FUEL CONSUMPTION RATIO (g/kwh)	630	490	490
TRANSMISSION RATIO	13/25	13/27	13/27
STEERING	Tiller Handle	Tiller Handle	Tiller Handle
LUBRICATION	Premix	Premix	Premix
STARTING SYSTEM	Recoil	Recoil	Recoil
EMERGENCY Flameout SWITCH	✓	✓	✓
STARTING PROTECTION	✓	✓	✓
THERMOSTATIC COOLING SYSTEM	✓	✓	✓
PROPELLER (STANDARD)	8-1/2 x 10-1/4	10-1/2 x 11	10-1/2 x 13
FUEL TANK	12L	23L	25L
TOOLS KIT	✓	✓	✓
SPARE SPARK PLUG	✓	✓	✓
WEIGHT(S)	30.5	52	52
WEIGHT (L)	31.5	54	54

Note: B=Back control, M=Manual start, L=Long Shaft

Untuk kepentingan perbaikan mutu mesin, hasil produk dan perkembangan kemajuan teknologi, spesifikasi dan dimensi dapat diperbarui. The product are subject of continous development and as result, their specification and dimension may change and differ in detail from those shown.