

CROWN NEO SPECIFICATION

Model	CGE 160 NEO	CGE 200 NEO
Engine Type	4 - stroke,25 inclined, single cylinder with air - cooled	
Bore x Stroke (mm)	68 x 45	68 x 54
Dispalcement (ml)	163	196
Compression Ratio	8.5 : 1	
Max Output (HP/rpm)	5.5 / 3600	6.5 / 3600
Max Torque (N.m/rpm)	10.8 / 2500	13.0 / 2500
Ignition System	Non - Contact transistorized ignition (T.C.I)	
Starting System	Recoil And hand operated	
Air Cleaner	Semi Dry, oil bath, dual, double silent and cyclone type	
Fuel Tank Capacity (Liter)	3.6	
Fuel Consumption (g/HP-hour)	270	
Oil Capacity (Liter)	0.6	
Packing Dimension (L x W x H)	400 x 345 x 385	
Net Weight (Kg)	15	16

Model	CBG 328 NEO
Engine	1E36F
Power	0.81kw / 6000rpm
Displacement (cc)	30.5
Fuel mix ratio	Gasoline 25 : two cycle oil 1
Tank capacity (L)	1.2
Engine package (mm)	290 x 280 x 410
Shaft package (mm)	1400 x 100 x 90
Weight package (kg)	10.5
Attachment	306mm 2T Blade

Model	CSU 80 NEO
Suction / Output Diameter (mm)	80
Power Requirment (HP)	6.5
Rotation (rpm)	3600
Capacity (m ³ /h)	40
Total head (m)	36
Suction head (m)	7
Package Dimensi (P x L x T) (mm)	395x240x250
Weight package (kg)	14

Model		CWP 20 NEO	CWP 30 NEO
WATER PUMP	Inlet / outlet	2" / 2"	3" / 3"
	Pump lift (m)	26	28
	Suction head (m)	8	8
	Output (Liter / min)	550	1000
ENGINE	Type	CGE 160 NEO	
PACKAGE DIMENSION	Dimension (LxWxH) (mm)	525 x 400 x 453	540 x 400 x 465
	Net weight (kg)	27	30

